

Model	Torque Normal		Max speed	Outside	All height	L1	L2	Bore diameter ore		Moment of Inertia GdA2 (kg*mA2)	Weight (kg)
No.	(Kq-m)	Max.	rpm.	dia	(D)			Min.	Max.		
L-035	0.15	0.05	6	16.1	20.15	6.68	6.77	4	8	0.1	0.02
L-050	0.45	0.15	4.5	27.6	42.55	15.64	11.25	6	16	1	0.14
L-070	0.9	0.3	3.6	34.23	49.92	19.3	11.3	6	20	3.3	0.25
L-075	1.5	0.5	3.6	44.6	52.88	20.36	11.74	8	26	9.1	0.45
L-090	2.4	0.8	3	53.58	53.22	20.7	11.8	10	28	15	0.66
L-095	3	1	3	53.58	62.36	25.22	11.9	10	28	17	0.78
L-099	6	2	3	64.55	76.47	29.72	17.01	12	36	42	1.35
L-100	7.5	2.5	3	64.55	86.47	34.72	17.01	12	36	43	1.53
L-110	15	5	2.5	84.28	106.32	43.08	20.14	12	38	147	3.3
L-150	30	10	2.5	95.28	112.95	44.6	23.73	16	46	258	4.43